





Product Specification

SOLINQ® 4mm SILVERLINE Connector



| | |
|-----------------------------|--|
| Rated voltage: | 1000V (IEC/CEI) |
| Rated current: | 30A (4mm ² , 6mm ²) |
| Typical Contact resistance: | ≅ 5mΩ |
| Diameter of pin or socket: | 4mm |
| Protection degree: | IP67 |
| Ambient temperature range: | -40C°...+85C° |
| Insulation material: | PC/PA |
| Contact material: | Copper, Silver plated (EpAg5~8) |
| Locking system: | Snap in |
| Safety class: | II |
| Certification: | TÜV UL Pending |
| Partnumber: | 46010CM (Male) 46011CF (Female) |



Crimping range :

| mm ² | AWG |
|-----------------|---------|
| 4 / 6 | 12 / 10 |

Stripping range cable

0,8 mm



Crimping (hand) tool:


Solinq® 72010CT

Packing quantity



Plastic bags 50/100/500 pieces
(Male/Female packed separately)

Contacts mounted on Reels
(for semi-automatic processing) :

Reels with 2000 contacts



Reel type subject to alterations





Product Specification

SOLINQ® 4mm PV-Installation Kit



PV-Installation Kit contains:

- 50 Male Solar connectors Solinq 4mm Silverline (incl. Silver plated contact pins)
- 50 Female Solar connectors Solinq 4mm Silverline (incl. silver plated contact pins)
- Solinq Crimping tool
- Solinq Wrench tools



Partnumber PV-Kit: PVKIT02