

## PRODUCTS INFORMATIONS

### Application

The 0.22 mm<sup>2</sup> series is constituted by flexible multi-conductors cables.

### Insulation colour code

1	White	11	Dark blue
2	Red	12	Pink
3	Yellow	13	White / Brown
4	Green	14	White / Violet
5	Grey	15	White / Green
6	Orange	16	White / Blue
7	Light blue	17	White / Grey
8	Brown	18	White / Yellow
9	Violet	19	White / Black
10	Black	20	White / Red

### Electrical properties

Working voltage : **200 V**  
Test voltage : **1200 V**

### Characteristics



.....Flame behaviour : IEC 60332-1 or NF C 32-070 Cat C2  
EN 50575 :2014+A1 :2016, Eca



..... Working temperature : - 10°C → + 70°C



..... Minimum bending radius: 10 x Ø



..... According to RoHS standard



This document is confidential, and is the property of CAE Groupe. CAE Groupe own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from CAE Groupe. The contents of this document must be disclosed to any other person or persons.

The characteristics related to this document are not contractual, and can be modified without warning.



[www.cae-groupe.fr](http://www.cae-groupe.fr)



# REF : 2XX0 B





TRANXALARM® flexible alarm cable



CAE  
SECURITE

FT 8 10/06/17 FR

## Products references

			
2020 B	2 x 0.22	3.10	15
2040 B	4 x 0.22	3.80	25
2060 B	6 x 0.22	4.40	36
2080 B	8 x 0.22	4.70	51
2100 B	10 x 0.22	5.50	60
2140 B	14 x 0.22	5.90	73
2200 B	20 x 0.22	6.70	113



This document is confidential, and is the property of CAE Groupe. CAE Groupe own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from CAE Groupe. The contents of this document must be disclosed to any other person or persons.

The characteristics related to this document are not contractual, and can be modified without warning.



[www.cae-groupe.fr](http://www.cae-groupe.fr)

