



PRODUCTS INFORMATIONS

Application

The 0.22 mm² series is constituted by flexible multiconductors cables.

Insulation colour code

Conductors 0.22 mm ²		Conductors 0.75 mm ²	
1	White	1	Red
2	Red	2	Black
3	Yellow		
4	Green		
5	Grey		
6	Orange		
7	Light blue		
8	Brown		

Electrical properties

Max. working Voltage : 0.22 mm² = 200 V
0.75 mm² = 250 V

Test voltage : 0.22 mm² = 1200 V
0.75 mm² = 2000 V

Mean electrical resistance at 20°C : 0.22 mm² = 96 Ω/km
0.75 mm² = 26 Ω/km

Characteristics



Flame behaviour :
IEC 60332-1 or NF C 32-070 Cat C2
EN50575:2014+A1:2016 Class Eca



Temperature range :
-10°C → +70°C



Minimum bending radius :
10 x Ø



According to RoHS standard



This document is confidential, and is the property of CAE Groupe. CAE Groupe own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from CAE Groupe. The contents of this document must be disclosed to any other person or persons.

The characteristics related to this document are not contractual, and can be modified without warning.



www.cae-groupe.fr



REF : MULTI 275 + n B

TRANXALARM® flexible alarm cable –
2x0,75 mm² + nx0,22 mm²



CAE
SECURITE

FT 4 02/10/17 DL

Products references

MULTI 275 + 4 B	(4 x 0.22) + (2 x 0.75)	5.5	62
MULTI 275 + 6 B	(6 x 0.22) + (2 x 0.75)	6.0	70
MULTI 275 + 8 B	(8 x 0.22) + (2 x 0.75)	6.7	79
MULTI 275 + 10 B	(10 x 0.22) + (2 x 0.75)	6.8	90



This document is confidential, and is the property of CAE Groupe. CAE Groupe own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from CAE Groupe. The contents of this document must be disclosed to any other person or persons.

The characteristics related to this document are not contractual, and can be modified without warning.



www.cae-groupe.fr

